

TECHNICAL SPECIFICATIONS

PRODUCT DIMENSIONS: <small>(All maximum or all minimum dimensions may not be attainable at the same time) (Consult ULMA for other dimensions)</small>	Seal jaw diameter	Ø 144 mm (5.7")	Ø 200 mm (7.9")
	Bag length	90 - 450 mm (3.5" - 17.5")	125 - 625 mm (5" - 24.5")
	Product length	60 - 350 mm (2.4" - 13.75")	90 - 500 mm (4.9" - 19.5")
	Product width	10 - 250 mm (4" - 9.75")	10 - 250 mm (4" - 9.75")
	Product height	5 - 70 mm (1/4" - 2.75")	5 - 150 mm (1/4" - 6")
SPEED	<small>(all maximum and minimum dimensions can not attain maximum speed)</small>	Up to 1000 packs/min <small>(dependent on product type, dimensions, and film type)</small>	
PACKAGING MATERIAL		Heat sealable films: BOPP (Bi-Oriented Polypropylene), PVC, polyester, cellulose, Cold sealing films / Versions for: Polyolefin shrinkable films, HDPE, laminated films	
FILM WIDTH CAPACITY		500 mm (op. 700 mm) (19.5") (op. 27.5")	
MAXIMUM ROLL DIAMETER		300 mm (12")	
CORE DIAMETER		76 mm (3")	
ELECTRICAL SPECIFICATIONS	Voltage	230 / 400 V Three-phase ±10% + Neutral + Ground – 50/60 Hz	
	Power consumption	8 kW - 16 Amp. / 380 V. • 14 Amp. / 230 V. (standard version)	
PNEUMATIC CONSUMPTION		From 0 to 50 l/m (0 to 1.75 CFM) / 6 bar (90 PSI) (depending on version and options)	
APPROXIMATE WEIGHT		1100 kg (2420 lb)	

ULMA reserves the right to change specifications without prior notice.



ULMA Packaging

Thanks to an experience of more than 50 years, we are a worldwide reference in the design and manufacturing of high-tech packaging systems and equipment.

More than 50 years evolving, innovating, perfecting our technology and our services. An extensive network that is available to offer you solutions anywhere in the world, and to fully satisfy customers that place their trust in us.

For additional information, please visit our website:

www.ulmapackaging.com

C0211

Global Packaging



ULMA Packaging, S. Coop.
 B° Garibai, 28 - Apdo. 145
 20.560 OÑATI (Gipuzkoa) SPAIN
 Tel.: +34 - 943 73 92 00
 Fax: +34 - 943 78 08 19
 Web: www.ulmapackaging.com
 e-mail: info@ulmapackaging.com

FR 500
 Flow Pack

| EN

Horizontal flow wrapping machine



The FR 500 machine represents the highest technology model in the range of ULMA horizontal wrappers.

Fully electronic, it integrates a multi-axis electronic control which synchronizes machine's main movements.

It is specially designed to be integrated into packaging systems in applications with medium and high speed productions.


The model FR 500 is completed with different feeders and autoloaders designed mainly for bakery and chocolate products.

TECHNICAL CHARACTERISTICS

- ▶ Stainless steel and cantilever construction.
- ▶ Electronic machine equipped with four independent servomotors (rotary jaws, sealing rollers, infeed conveyor and motorized reel holder) synchronized by an electronic multi-axis control)
- ▶ Four pairs of sealing rollers.
- ▶ Automatic reel change.
- ▶ Pneumatic fixing of film reel.
- ▶ 10" colour touch screen to adjust machine parameters, diagnostics and reporting.
- ▶ Infeed conveyor with chain at one side.
- ▶ Top motorized belt system at exit belt.
- ▶ Empty and badly sealed package rejector.
- ▶ Complete range of infeed conveyors depending on the application and product.

MAIN OPTIONAL ELEMENTS

- ▶ Printing system.
- ▶ Cold plate sealing rollers.
- ▶ Overhead and side devices.
- ▶ Aspiration system between rollers.
- ▶ "D-Cam" type jaw.
- ▶ Gusseting device by mechanical or air system.



FR 500



HMI panel with color graphics



Cross cut sealing system with 2 jaws per shaft



Double film roll holders with automatic roll splicing



Misplaced product rejector in the infeed conveyor