

Motor power	120 W 150-370 W	Up to a belt width of 400 mm As from a belt width of 500 mm
IP rating	IP65	NEMA 4
Belt speeds	0.2 m/s 0.4 m/s 0.6 m/s 1.0 m/s	Ex factory firmly adjustable from -60% to +30%.
Transport height	900 ±50 mm	
Options	Facts	Details
Higher Level Compliance package	Sensor – Higher level compliant fail safe system: Warning device, self-monitoring – Rejection system with reject bin and cover to be selected separately	Meets the requirements of large retail chains only available for INTUITY
Rejection system	Pusher Air-jet nozzle respectively with reject bin and protective cover in Size 1 Size 2 requires compressed air of 6-8 bar	for products of up to 5 kg for products of up to 0.5 kg for products up to 250 mm long for products up to 450 mm long Plug NW 7.2
Sensor packages for rejection systems	Compressed air monitoring Rejection monitoring Fill level monitoring for reject bin	respectively in Higher Level Compliance package included
Signal combination	– 4 signal lamps and 1 horn SK-R-4+1 (stand mounting) mounted onto stand incl. cabling and assembly aid – Yellow signal lamp and horn SK-R (stand mounting) mounted onto stand incl. cabling and assembly aid	Red: Error Yellow: Metal detected Green: Ready for operation Blue: AuditCheck Signal horn when error is displayed Error Error and metal display
Conveyor speeds	Variable conveyor speed	adjustable, depending on the product
Light sensor on feeding belt	For product detection	For counting of the products and for calculation of the Overall Equipment Efficiency (OEE)
Remote operating unit	For separate mounting of coil and control, with mounting unit, blind cover and 10 m connecting cable	only available for INTUITY
Voltage transformer	115 V AC (±10 %) 60 Hz incl. power cable	US version
Interfaces	Ethernet (TCP/IP) RS232, RS485, WLAN, Profibus	Only available for GLS
Lateral guiding bars	Height: 50 mm	For alignment of products
Mobile conveyor	Four lockable guide rollers	For flexible use of the system

IP rating	IP66/69	GLS: Special coil version INTUITY: Tunnel comes standard in IP66/69
Other conveying heights	700, 800, 1,000 ±50 mm	With caster 750, 800, 1,000 ±50 mm

Info graphics



Symbols

IP65 protection	IP66 protection	IP69 protection	Stainless steel	Hygienic design